

PROTECRETE
INDUSTRIAL PRICE LIST

Effective October 1, 2006
Subject to change without notice

Product	Catalog No.	Industrial List/Gallon	Typical square feet per gallon
① PROTECRETE DENSIFIER <i>formerly CDS Concrete Densifier Sealer</i> Waterproofs, densifies new or existing portland concrete	5-175 gallons	56.00	200s.F.
	180-715 gallons	54.00	range: 150-400
1 DENSIFIER PLUS REPELLER ¹ <i>formerly D+SRT</i> Adds a surface treatment for easier cleaning	5-175 gallons	58.00	200 S.F.
	180-715 gallons	56.00	range: 150-400
DENSIFIER FOR REBAR <i>formerly D+SPP</i> Adds a steel corrosion inhibitor	5-175 gallons	58.00	100 S.F.
	180-715 gallons	56.00	
DENSIFIER PLUS CLEANER <i>formerly D+PCF</i> Adds a penetrating cleaner	5-175 gallons	58.00	200 S.F.
	180-715 gallons	56.00	
1 DENSIFIER WITH SURFACE GLOSS Adds a repellent finish with an long lasting shine	5-175 gallons	58.00	200 S.F.
	180-715 gallons	56.00	range: 200-400
② PROTECRETE EFF-CLEAN A safer, more effective solution for removing efflorescence	5-175 gallons	54.00	varies
	180-715 gallons	52.00	
③ PROTECRETE HEAVY DUTY TOPPING An extraordinarily hard cementitious coating/topping	5-175 gallons	67.00	75-300 S.F.
	180-715 gallons	65.00	
④ PROTECRETE MIX WATER CONDITIONER *** An additive for mix water for extraordinary durability	5-175 gallons	46.00	10 oz per 100lbs of
	180-715 gallons	44.00	Portland cement
⑤ PROTECRETE RADIANCE <i>New!</i> Glossy finish with the Repeller added to it for less staining	5-175 gallons	64.00	300 S.F.
	180-715 gallons	62.00	range: 200-400
⑥ PROTECRETE REPELLER <i>formerly SRT</i> For protection and easier cleaning of many surface types	5-175 gallons	54.00	200-500 S.F.
	180-715 gallons	52.00	
⑦ PROTECRETE REDEEMER <i>formerly Surface Saver</i> Glossy finish. Also for crack repair, sand consolidation	5-175 gallons	56.00	300 S.F.
	180-715 gallons	54.00	range: 75-300
** PROTECRETE ASPHALT SEALER <i>New!</i> For ultimate protection of asphalt.	5-175 gallons	60.00	200 S.F.
	180-715 gallons	58.00	range: 150-350
⑧ PROTECRETE VITRITRED An anti-slip solution for slip resistance on slick surfaces	5-175 gallons	86.00	400 S.F.
	180-715 gallons	84.00	
⑨ PROTECRETE WOOD PROTECTOR A long-lasting UV protectant sealer for wood surfaces	5-175 gallons	56.00	200 S.F.
	180-715 gallons	54.00	range: 100-400
┘ PROTECRETE LIQUID APPLIED MEMBRANE Waterproofs non-traffic surfaces like roofs	5-175 gallons	55.00	depends on
	180-715 gallons	53.00	thickness

¹For green (new) concrete only.

TERMS: Initial order (and all international orders) are cash in advance of delivery. Net 15/30 days subject to credit approval. Service charge of 2% per month will be added to any overdue accounts. Orders over 720 gallons receive an additional \$1 per gallon discount.

RETURNED GOODS POLICY: If authorization for return is given, returned goods will be subject to inspection and a 25% restocking charge. Returns must be shipped prepaid and are subject to deductions of original freight out (10%) and repackaging fees (15%). No cash refunds will be issued on returned merchandise, and all credits issued will be applied to future orders. If returned merchandise is not salable, the return will not be accepted and no credit.

DAMAGED GOODS: All products are shipped in good condition. If containers are damaged when received, claims must be filed against the freight carrier.

SHIPPING: Prepaid. Billed to distributor. F.O.B. Dallas, TX.

APPROXIMATE SHIPPING WEIGHTS OF LIQUID CONTAINERS:
5-gallon pail: 50 pounds 55-gallon drum: 550 pounds

PALLETIZING INFORMATION:
Pails per pallet: 24 Drums per pallet: 4

Possession of this list does not constitute an agreement to sell

Manufacturer of Concrete Enhancement and Protection Products · Member of the American Concrete Institute

APPLIED CONCRETE TECHNOLOGY, INC.

Post Office Box 548, Grayslake, IL 60030 847.548.2444 800.228.6694 FAX 847.548.2555 WWW.PROTECRETE.COM